designed and created for your needs

RENTAL LINE STAGE 5

power and innovation



STAGE 5 CERTIFIED

Fuel Tank capacity

din .

States a

For TRIME





MGTP 20 SSY MV



WATER cooled

1500 RPM

YANMAR

NOISE

level

RENTAL LINE

DIESEL

SINGLE

phase

THREE

phase

SINGLE

phase



APPLICATIONS











FEATURES

- Built in fuel tank
- Bunded tank
- 12V Battery
- Battery switch
- Forklift pocket
- Central lifting eye
- 👳 Exhaust gas silencer
- Soundproof canopy
- 2 way valve for external fuel tank connection



Code		RP248-20TS7
Technical Data		
PRP Prime Power	kVA	20
LTP Limited Time Power	kVA	21
Prime Power ($\cos \phi = 0.8$)	kW	16
Limited Time P. ($\cos \phi = 0.8$)	kW	16.8
Three-phase Voltage	V	400
Single-phase Voltage	V	230 + 115
Power factor (cos φ)		0.8
Frequency	Hz	50
RPM		1500

Generator		
LINZ / MECC ALTE / STAMFORD		
Insulation Class		Н
Mechanical protection		IP23
Engine		
Туре	YANMAR 4TNV88	
EU Emission Stage		Stage V
N° cylinders		4
Displacement	cm ³	2216
Speed regulation		Mechanical
Cooling		Water
Fuel		Diesel
Oil sump capacity	lt.	10.6
Fuel Consumption		
Fuel Tank capacity	lt.	136
Fuel consumption 75% load PRP	l/h	4,0
Running time	h	32
Noise Level		
Noise level	Lwa	88
Acoustic pressure level 7m	dBA	63
Dimensions & Weight		
Dry weight	Kg	908
Dimensions (L. x W. x H.)	mm	1850 x 900 x 1510
Distribution panel:		
1x 32A 400V EEC with MCB		
2x 32A 230V EEC with MCB + ELCB		
2x 16A 230V EEC with MCB + ELCB		
3x 32A 115V EEC with MCB		
1x 16A 115V EEC with MCB		
Hardwire		
ELR		
On board control panel equipped with:		
DSE 7310		
ON/OFF switch		
Safety cover for DSE 3110 + ON/OFF switch		
Main circuit breaker		
Earth leakage relay		
Remote start/stop connector		
Emergency stop		



Trime UK Ltd | 1 Redwing Court, Falcon Road, Hinchingbrooke Business Park, Huntingdon PE29 6FG 01480 220500 | www.trimeuk.com | sales@trimeuk.com

Site tow trailer